


HTML & XHTML

Quick Reference, 6th Edition

HTML/XHTML Tag Syntax



QuickRef Syntax

```
<tag name> ... (intervening content) ...
</end tag>
list of attributes=value types
(string, color, ...)
<subordinate tag name> ... </end tag>
list of attributes=value types
```

XHTML-Specific Syntax

All tag names must be in lowercase
(`<HTML>` is not acceptable, for example).

All tags must have an end tag. For HTML empty tags, such as `
`, either append an end tag (`
</br>`, for example) or use the alternative form that combines the empty tag and its end tag (`
`, for example).

Enclose all attribute values within quotes (`size="10 px"`, for example).

All attributes must have a value. Repeat attribute name as value, as needed (`ismap="ismap"`, for example).

Core Attributes

Core attributes can be used with any tag except those marked with an asterisk (*), with which none or some of the core attributes apply. See Appendix B and main text for details.

```
class=name
dir=dir
id=name
lang=language
onclick=applet
ondblclick=applet
onkeydown=applet
onkeypress=applet
onkeyup=applet
onmousedown=applet
onmousemove=applet
onmouseout=applet
onmouseover=applet
onmouseup=applet
style=style
title=string
```

Skeletal Tags

```
<body> ... </body>
alink=color
background=url
bgcolor=color
bgproperties=value
leftmargin=n
link=color
onblur=applet
onfocus=applet
onload=applet
onunload=applet
text=color
topmargin=n
vlink=color
<comment> ... </comment>
<frameset> ... </frameset>*
border=n
bordercolor=color
cols=list
frameborder=value
framespacing=n
onblur=applet
onfocus=applet
onload=applet
onunload=applet
rows=list
<frame> ... </frame>*
bordercolor=color
frameborder=n
longdesc=url
marginheight=n
marginwidth=n
noresize
scrolling=type
src=url
<noframes> ... </noframes>
<head> ... </head>*
profile=url
<html> ... </html>*
version=string
```

Header Tags

```
<base>*
href=url
target=name
<basefont>*
color=color
face=name
size=value
<isindex>*
action=url
prompt=string
<link>*
charset=charset
href=url
hreflang=language
media=list
rel=relation
rev=relation
type=string
<meta>*
charset=charset
content=string
http-equiv=string
scheme=scheme
<nextid>*
n=n
<style> ... </style>*
media=list
type=type
<title> ... </title>*
```

Hyperlinks

```
<a> ... </a>
accesskey=char
charset=encoding
coords=list
href=url
hreflang=language
rel=relationship
rev=relationship
shape=shape
tabindex=value
target=name
type=type
```

Text Markup Tags

Physical Tags

```
<b> ... </b>
<big> ... </big>
<blink> ... </blink>
<i> ... </i>
<s> ... </s>
<small> ... </small>
<strike> ... </strike>
<sub> ... </sub>
<sup> ... </sup>
<tt> ... </tt>
<u> ... </u>
```

Content-Based Tags

```
<abbr> ... </abbr>
<acronym> ... </acronym>
<cite> ... </cite>
<code> ... </code>
<del> ... </del>
  cite=url
  datetime=date
<dfn> ... </dfn>
<em> ... </em>
<ins> ... </ins>
  cite=url
  datetime=date
<kbd> ... </kbd>
<samp> ... </samp>
<strong> ... </strong>
<var> ... </var>
```

Forms

```
<form> ... </form>
  accept-charset=list
  action=url
  enctype=encoding
  method=type
  onreset=applet
  onsubmit=applet
  target=name
<button> ... </button>
  accesskey=char
  disabled
  name=name
  onblur=applet
  onfocus=applet
  tabindex=n
  type=type
  value=string
<fieldset> ... </fieldset>
<input type=button>
  accesskey=char
  disabled
  name=name
  notab
  tabindex=n
  taborder=n
  value=string
<input type=checkbox>
  accesskey=char
  checked
  disabled
  name=name
  notab
  readonly
```

```
  tabindex=n
  taborder=n
  value=string
<input type=file>
  access=list
  accesskey=char
  disabled
  maxlength=n
  name=name
  notab
  onblur=applet
  onchange=applet
  onfocus=applet
  onselect=applet
  readonly
  size=n
  tabindex=n
  taborder=n
  value=string
<input type=hidden>
  name=name
  value=string
<input type=image>
  accesskey=char
  align=type
  alt=string
  border=n
  disabled
  name=name
  notab
  src=url
  tabindex=n
  taborder=n
  usemap=url
<input type=password>
  accesskey=char
  disabled
  maxlength=n
  name=name
  notab
  onblur=applet
  onchange=applet
  onfocus=applet
  onselect=applet
  readonly
  size=n
  tabindex=n
  taborder=n
  value=string
<input type=radio>
  accesskey=char
  checked
  disabled
  name=name
  notab
  readonly
  tabindex=n
  taborder=n
  value=string
<input type=reset>
  accesskey=char
  disabled
  notab
  tabindex=n
  taborder=n
  value=string
<input type=submit>
  accesskey=char
  disabled
  name=name
  notab
  tabindex=n
  taborder=n
  value=string
<input type=text>
  accesskey=char
  disabled
  maxlength=n
  name=name
  notab
  readonly
  size=n
  tabindex=n
  taborder=n
  value=string
<keygen>
  challenge=string
  name=name
<label> ... </label>
  accesskey=char
  for=name
  onblur=applet
  onfocus=applet
<legend> ... </legend>
  accesskey=char
  align=position
<select> ... </select>
  disabled
  multiple
  name=name
  onblur=applet
  onchange=applet
  onfocus=applet
  size=n
  tabindex=n
<option> ... </option>
  disabled
  label=string
  selected
  value=string
<optgroup> ... </optgroup>
  disabled
  label=string
<textarea> ... </textarea>
  accesskey=char
  cols=n
  disabled
  name=name
  onblur=applet
  onchange=applet
  onfocus=applet
  onselect=applet
  readonly
  rows=n
  tabindex=n
  wrap=type
```

Rules, Images, and Multimedia

```
<bgsound>
  loop=integer
  src=url

<img>
  align=horizontal-align
  alt=text
  border=integer
  controls
  dynsrc=url
  height=integer
  hspace=integer
  ismap
  longdesc=url
  loop=integer
  lowsrc=url
  name=name
  onabort=applet
  onerror=applet
  onload=applet
  src=url
  start=start
  usemap=url
  vspace=integer
  width=integer

<map> ... </map>
  name=name

<area>
  accesskey=char
  alt=string
  coords=list
  href=url
  nohref
  notab
  onblur=applet
  onfocus=applet
  shape=shape
  tabindex=integer
  taborder=integer
  target=name

<marquee> ... </marquee>
  align=horizontal-align
  behavior=style
  bgcolor=color
  direction=dir
  height=integer
  hspace=integer
  loop=integer
  scrollamount=integer
  scrolldelay=integer
  vspace=integer
  width=integer
```

Formatted Lists

```
<dir> ... </dir>
  type=bullet
  <li> ... </li>
    type=format
    value=n

<dl> ... </dl>
  compact
  <dd> ... </dd>
  <dt> ... </dt>

<menu> ... </menu>
  type=bullet
  <li> ... </li>
    type=format
    value=n

<ol> ... </ol>
  compact
  start=n
  type=format
  <li> ... </li>
    type=format
    value=n

<ul> ... </ul>
  compact
  type=bullet
  <li> ... </li>
    type=format
    value=n
```

Tables

```
<table> ... </table>
  align=horizontal-align
  background=url
  bgcolor=color
  border=integer
  bordercolor=color
  bordercoldownk=color
  bordercolorlight=color
  cellpadding=integer
  cellspacing=integer
  cols=integer
  frame=type
  height=integer
  hspace=integer
  nowrap
  rules=edges
  summary=string
  valign=vertical-align
  vspace=integer
  width=integer

<caption> ... </caption>
  align=horizontal-align
  valign=vertical-align

<colgroup>
  align=horizontal-align
  char=character
  charoff=integer
  span=integer
  valign=vertical-align
  width=integer

<col>
  align=horizontal-align
  char=character
  charoff=integer
  span=integer
  valign=vertical-align
  width=integer

<tbody> ... </tbody>
  align=horizontal-align
  char=character
```

```
  charoff=integer
  valign=vertical-align

<tfoot> ... </tfoot>
  align=horizontal-align
  char=character
  charoff=integer
  valign=vertical-align

<thead> ... </thead>
  align=horizontal-align
  char=character
  charoff=integer
  valign=vertical-align

<tr> ... </tr>
  align=horizontal-align
  background=url
  bgcolor=color
  bordercolor=color
  bordercoldownk=color
  bordercolorlight=color
  char=character
  charoff=integer
  nowrap
  valign=vertical-align

<td> ... </td>
  abbr=string
  align=horizontal-align
  axis=string
  background=url
  bgcolor=color
  bordercolor=color
  bordercoldownk=color
  bordercolorlight=color
  char=character
  charoff=integer
  colspan=integer
  headers=list
  height=integer
  nowrap
  rowspan=integer
  scope=scope
  valign=vertical-align
  width=integer

<th> ... </th>
  abbr=string
  align=horizontal-align
  axis=string
  background=url
  bgcolor=color
  bordercolor=color
  bordercoldownk=color
  bordercolorlight=color
  char=character
  charoff=integer
  colspan=integer
  headers=list
  height=integer
  nowrap
  rowspan=integer
  scope=scope
  valign=vertical-align
  width=integer
```

Executable Content

```
<applet> ... </applet>*
  align=position
  alt=string
  archive=url
  code=class
  codebase=url
  height=n
  hspace=n
  mayscript
  object=data
  vspace=n
  width=n

<param> ... </param>
  name=name
  type=type
  value=string
  valuetype=type

<embed>
  align=position
  border=n
  height=n
  hidden
  hspace=n
  name=name
  palette=value
  pluginspage=url
  src=url
  type=type
  units=type
  vspace=n
  width=n

<noembed> ... </noembed>
<noscript> ... </noscript>
<object>
  align=position
  archive=list
  border=n
  classid=url
  codebase=url
  codetype=type
  data=url
  declare
  height=n
  hspace=n
  name=name
  notab
  shapes
  standby=string
  tabindex=n
  type=type
  usemap=url
  vspace=n
  width=n

<param> ... </param>*
  name=name
  type=type
  value=string
  valuetype=type

<script> ... </script>*
  charset=encoding
  defer
  language=name
  src=url
  type=encoding

<server> ... </server>
```

Content Presentation and Flow

```
<address> ... </address>
<bdo> ... </bdo>
<blockquote> ... </blockquote>
  cite=url
<br>*
  clear=margin
<center> ... </center>
<div> ... </div>
  align=type
  nowrap
<font> ... </font>*
  color=color
  face=list
  size=value
<hn> ... </hn> (n=1-6)
  align=type
<hr>*
  align=type
  color=color
  noshade
  size=pixels
  width=value or percent
<iframe> ... </iframe>*
  align=position
  frameborder=value
  height=n
  longdesc=url
  marginheight=n
  marginwidth=n
  scrolling=type
  src=url
  width=n

<listing> ... </listing>
<nobr> ... </nobr>
<p> ... </p>
  align=position
<plaintext>
<pre> ... </pre>
  width=n
<q> ... </q>
  cite=url
<span> ... </span>
<wbr>
<xmp> ... </xmp>
```

Netscape-Only Layout Tags

```
<layer> ... </layer>
  above=name
  background=url
  below=name
  bgcolor=color
  clip=edge
  left=n
  name=name
  src=url
  top=n
  visibility=value
  width=n
  z-index=n

<multicol> ... </multicol>
  cols=n
  gutter=n
  width=n

<spacer>
  align=position
  height=n
  size=n
  type=type
  width=value
```